# **MATERIAL SAFETY DATA SHEET**

# **Product: CRAQUELURE STEP 2**

### PHYSICAL DATA:

APPEARANCE......CREAMY YELLOW LIQUID

SOLUBILITY......UNLIMITED DISPERSION IN WATER

CHEMICAL REACTIVITY......WATER BASED MODIFIED DEXTRIN

BOILING POINT.....APPROX. 100 DEG.CELSIUS

### FIRE AND EXPLOSIVE HAZARDS:

FLAMMABILITY: Being water based, the product can be regarded as non-flammable, however, the dried coating will burn, producing carbon monoxide, carbon dioxide and sometimes oxides of nitrogen accompanied by dense black smoke. Flashpoint is not applicable with no explosion limits.

EXTINGUISHING MEDIA: Only for dried material. Water, carbon dioxide or dry chemicals. Fire fighters should wear self-contained breathing apparatus to avoid inhalation of smoke vapor.

#### **HEALTH HAZARD DATA**

The product is not regarded as hazardous and for normal spillages on skin, clothing, etc. washing with water is adequate.

# EFFECT OF PROLONGED EXPOSURE:

Contact with skin: may cause irritation and/or rash. Contact with eyes: may cause irritation and/or redness.

#### **EMERGENCY AND FIRST AID PROCEDURES**

For ingestion: drink plenty of water or induce vomiting. Call for immediate medical attention.

For skin: wash effected area with soap and water.

For eyes: flush with copious volumes of clean water. Call for immediate medical attention.

# **SPILLAGES OR LEAKS**

Clean up with water before allowing to dry. Absorb spills with sand and/or rags. Craquelure Step 2 can be attacked by bacteria and is not particularly toxic to fish or plants, but waste should not be discharged without treatment. After dilution residues can be disposed in a biological sewerage plant.

## PROTECTION EQUIPMENT

Normal protective clothing, i.e. gloves & overalls, are usually adequate, safety glasses are recommended. When working with Craquelure Step 2 ensure adequate ventilation.

#### STORAGE AND HANDLING

To ensure safe storage of Craquelure Step 2, containers should be well sealed to prevent evaporation of water. Craquelure Step 2 should be stored under cover and at a temperature above freezing point. A storage period of not more than six months under these conditions is recommended.

#### APPLICRAFT PRODUCTS

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for particular applications or the results obtained therefrom. Full-scale testing and end product performances are the responsibility of the user. APPLICRAFT shall not be held liable and the customer / user assumes all risks and liability of any use or handling beyond our direct control. The seller makes no warranties, express or implied, including but not limited to the implied warranties of merchantability and fitness for any particular purpose



Applicraft, Hillcrest, Guildford Road, Ottershaw. Surrey. KT16 0QL. UK

www.applicraft.co.uk email: info@applicraft.co.uk

re: (+44) 01932 872572

Fax: (+44) 01932 874501